

Description

Indoor drop coaxial cable - 75 Ohm
Indoor installation cable (Screening Class B)



Data Sheet

DKT-SAT4G



0,80 (Cu)	3,50 (PEG)	3,60 (Al/Pet/Al)	4,00 (CuSn)	5,00 (PVC)
--------------	---------------	---------------------	----------------	---------------

Constructive data

Inner conductor of plain copper	(Cu)	0,80 ± 0,02 mm
Dielectric of physical foam polyethylene	(PEG)	3,50 ± 0,10 mm
Water repellent sealing (dielectric)	(Jelly1)	
Aluminium/Polyester/Aluminium tape longitudinally overlapped	(Al/Pet/Al)	
Braid of tinned copper wires	(CuSn)	
Braid optical coverage (IEC 96-1)		47 %
Diameter under Sheath		4,00 mm
Outer sheath of Polyvinylchloride - grey (RAL 7035) - lead-free (Q1B)	(PVC)	5,00 ± 0,10 mm

Printed each meter by black ink-jet :

CAVEL DKT SAT 4G GAS INJECTED 75 Ohm ass m

(a=year, ss=week) (m=meter marking)

Electrical data

Characteristic impedance (@ 200 MHz)	75 ± 3	Ohm
Capacitance (@1kHz)	52 ± 2	pF/m
Velocity factor	85 %	
Outer conductor resistance	26	Ohm/km
Loop resistance	61	Ohm/km
Insulation voltage of the sheath (spark test)	2,50	kV
Maximum current (I _{eff})	4,00	A

Structural return loss (SRL)

5 - 470 MHz	>30 dB
470 - 1000 MHz	>28 dB
1000 - 2000 MHz	>26 dB
2000 - 3000 MHz	>22 dB

Screening attenuation (SA)

30 - 1000 MHz	>80 dB
1000 - 2000 MHz	>80 dB
2000 - 3000 MHz	>75 dB

Transfer impedance

5 - 30 MHz < 1,2 mOhm/m

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

11/07/2008

Responsible

PierPaolo Piccinini

Description

Indoor drop coaxial cable - 75 Ohm

Indoor installation cable (Screening Class B)

Coaxial Cables

CAVEL®

since 1968

Data Sheet

DKT-SAT4G

Attenuation (at 20°C):

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	2,30	862	23,30
10	2,80	1000	25,20
30	4,60	1750	34,50
50	5,60	2150	38,20
200	10,90	2400	40,20
300	13,70	3000	45,80
470	17,00		

Mechanical data


Weight of copper conductors	8,90	kg/km
Total weight of cable	23,60	kg/km
Minimum bending radius (single/repetead bending)	25/50	mm
Max. cable pulling strenght	90	N

Attenuazione di schermatura / Screening Attenuation

Cavo classe B / B Class Cable

Cavo tipo / Cable type : DKT SAT 4G

Data / Date : 27-09-2006



ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

11/07/2008

Responsible

PierPaolo Piccinini