

0,41 (FeCu)	1,90 (PEG)	2,07 (Al/Pet/Al/Sur)	2,47 (CuSn)	2,59 (Al/Pet)	6,90 x 3,60 (PVC)	5,10 (PVC)
----------------	---------------	-------------------------	----------------	------------------	----------------------	---------------

Constructive data

Inner conductor of copper clad steel	(FeCu)			0,41 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)			1,90 ± 0,10	mm
Aluminium/Polyester/Aluminium/Surlyne tape longitudinally overlapped and bonded to the dielectric	(Al/Pet/Al/Sur)				
Braid of tinned copper wires	(CuSn)				
---				70 %	
Outer Aluminium/Polyester tape longitudinally overlapped	(Al/Pet)	23	x	30/19	m/μm
Diameter under Sheath				2,47	mm
Inner sheath of Polyvinylchloride white (PVQ1BI) lead-free (Q1B)	(PVC)			3,60 ± 0,10	mm
Outer sheath of Polyvinylchloride - white (PVQ1BI) - lead-free (Q1B)	(PVC)	6,90	x	5,10 ± 0,10	mm

Printed each meter by black ink-jet :

CAVEL DKT MINI 2EWH GAS INJECTED 75 Ohm ass

(ass=year week)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date

Responsible