

Description

Indoor drop coaxial cable - 75 Ohm

Indoor installation cable
(Screening Class A)**Data Sheet****DG11CUB**

Ø	1,63	7,20	7,30	7,78	10,10
	(Cu)	(PEG)	(Cu/Pet)	(Cu)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EN 50117-2-4

Reaction to Fire

EN50575

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,63 ± 0,03	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 7,20 ± 0,10	mm
Outer Copper/Polyester tape longitudinally overlapped	(Cu/Pet)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of annealed copper wires	(Cu)		
Braid optical coverage (IEC 96-1)		46	%
Diameter over Braid		Ø 7,78	mm
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 10,10 ± 0,15	mm
Printed each meter by blue ink-jet :			

CAVEL DG11CUB MADE IN ITALY 75 Ohm Euroclass Eca EN50117-2-4 CEI-UNEL 36762 C-4 (U0 = 400V)
gggaan m

(ggg=day)(aa=year)(n=batch) (m=meter marking)

Physical data

Weight of copper conductors	34,50	kg/km
Total weight of cable	94,21	kg/km
Minimum bending radius (single/repetead bending)	100	mm
Maximum cable pulling strength	300	N
Minimum installation temperature	-5	°C
Operating temperature	-40 / +80	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 2	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		8,50	Ohm/km
Outer conductor resistance		11,60	Ohm/km
Loop resistance		20,10	Ohm/km
Sheat Insulation voltage (spark test)		5	kV
Maximum current (Ieff)		16	A

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

23/03/2017

Responsible

PierPaolo Piccinini

Description

Indoor drop coaxial cable - 75 Ohm

Indoor installation cable

(Screening Class A)

Coaxial Cables

CAVEL®

since 1968

Data Sheet**DG11CUB****Structural return loss (SRL)**

5 - 470 MHz	>30 dB
470 - 1000 MHz	>28 dB
1000 - 2000 MHz	>23 dB
2000 - 3000 MHz	>20 dB


Screening Attenuation (SA)

SA-Class A

30 - 1000 MHz	>85 dB
1000 - 2000 MHz	>75 dB
2000 - 3000 MHz	>65 dB

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,10	862	12,30
10	1,50	1000	13,20
30	2,20	1750	17,90
50	2,80	2150	20,10
200	5,60	2400	21,00
300	6,90	3000	24,50
470	8,80		

Attenuazione di schermatura / Screening Attenuation**Cavo classe A / A Class Cable****Cavo tipo / Cable type : DG11CUB****ITALIANA CONDUTTORI s.r.l.**

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date

23/03/2017

Responsible

PierPaolo Piccinini

Description

Indoor drop coaxial cable - 75 Ohm

Indoor installation cable

(Screening Class A)

**Data Sheet****DG11CUB****Connectors**

3,5/12M-TL232	3,5/12" connector, male, for UNDERGROUND (Hardline) installation -
5/8MU-TL232	5/8" connector, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 69,0 mm x 20,5 mm
F163	Series F Crimp, F Crimp, for INDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm
FA17/73	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 33,0 mm x 14,5 mm
FC11QM	Series F Compression, Quick Mount, for OUTDOOR installation
FM-TL232	Series F, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 76,0 mm x 31,0 mm
IEC14M-32	Series IEC (toolless), male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 64,5 mm x 21,0 mm
NM-32	N Connector, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 62,5 mm x 21,0 mm
SP-32	Adapter, Splice Connector, for UNDERGROUND (Hardline) installation
SR01-32	Adapter, for 11/50 - RG11, for UNDERGROUND (Hardline) installation

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date**23/03/2017****Responsible****PierPaolo Piccinini**