

DATA SHEET

Item no. 99909421-01

Connector type F-59-CX3 3,9
For cable Ören Kablo RG59

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating (measured)	Cable data
(calculated)	Cable data
Transfer Impedance (CoMeT)	<2,5 mΩ/m @ 5-30MHz
	<0,07 mΩ/item @ 5-30MHz
Shielding Effectiveness (CoMeT)	>125 dB @ 30- 862MHz
	>118 dB @ 862-3000MHz



All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.

Return Loss (IEC 61169-1)
(RF Analyzer R and S ZVB 8)

	Better than	Typical
0.3 - 500 MHz	-28 dB	-31,2 dB
500 - 860 MHz	-28 dB	-30,6 dB
860 - 1000 MHz	-27 dB	-30,1 dB
1000 - 1750 MHz	-26 dB	-29,3 dB
1750 - 2150 MHz	-26 dB	-29,3 dB
2150 - 3000 MHz	-26 dB	-28,6 dB

Insertion Loss Max.

	Better than	Typical
0.3 - 500 MHz	-0,06 dB	-0,01 dB
500 - 860 MHz	-0,06 dB	-0,01 dB
860 - 1000 MHz	-0,06 dB	-0,01 dB
1000 - 1750 MHz	-0,07 dB	-0,02 dB
1750 - 2150 MHz	-0,07 dB	-0,02 dB
2150 - 3000 MHz	-0,09 dB	-0,04 dB

Temperature

Installing	-5° to +50° C
Operating	-40° to +100° C
Storing	-40° to +100° C

Intermodulation

	IM3	IP3-value
3rd Order (@2x100mW)	<-140 dBc	>90 dBm

Inner Conductor Resistance

@ 1 A DC	Cable data
----------	------------

Sealing Test

(IEC IP-code)	IP X8 1 meter / 24 hours
---------------	--------------------------

Insulation Resistance

@ 500 VDC	Cable data
-----------	------------

O-rings

EPDM

Dielectric Strength

DC Test Voltage	Cable data
-----------------	------------

Base Material

Body Parts	Brass CuZn39Pb3 / POM
Inner Conductor	Cable data

Max. Tensile Strength

Overall	260 N
	26,5 Kg.

Plating

Body Parts	Nitin-6
Inner Conductor	Cable data

Torsional Strength

(Connector / Cable)	NATM*
---------------------	-------

Test performed by

Søren B. Sørensen

Date of release

March 15, 2010

Remarks

* Not Able To Measure(NATM): The cable starts to twist without the connector loosing its grip.

ISO 9001:2000 / ISO 14001 certified

Distributor:

CABELCON
connectors

Corning Cabelcon ApS, Industriparken 10, DK 4760 Vordingborg
Tel: +45 55 98 55 99 · Fax: + 45 55 98 55 04
E-mail: cabelcon@cabelcon.dk · www.cabelcon.dk

Form 041 rev 7