

Description

Local Area Network Cable

Cat. 6A U/UTP 4x2xAWG23/1


Coaxial Cables

CAVEL®

since 1968

Data Sheet

LAN6A40



Ø	0,57	1,00	6,60
	(Cu)	(PE)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EIA-TIA 568C.2	ISO/IEC 11801	IEC 61156-5	EN 50173-1
EN 50288-11-1 Draft			

Reaction to Fire

IEC 60332-1	EN50575
-------------	---------

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T

IEEE 802.5 16 MB: ISDN; FDDI; ATM

Construction data

4 pairs with conductor of bare copper wires	(Cu)	Ø 0,57	mm
Insulation of solid Polyethylene	(PE)	Ø 1,00	mm
Lay Length of Pairs		80	mm
Cross separator in Polyethylene	(PE)		
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 6,60	mm

Printed each meter by blue ink-jet :

CAVEL LAN 6A40 MADE IN ITALY CAT 6A U/UTP 4x2xAWG23 - Euroclass Eca ISO-IEC 11801 EN50173
CEI-UNEL 36762 C-4 (U0 = 400V) gggaan m

(ggg=day)(aa=year)(n=batch) (m=meter marking)

Physical data

Weight of copper conductors	18,56	kg/km
Total weight of cable	45,20	kg/km
Minimum bending radius x1/n	35/70	mm
Maximum tensile strength during the installation	100	N
Installation temperature	0 / +50	°C
Operating temperature	-20 / +60	°C

Electrical data

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

30/05/2017

Responsible

Alberto Scardovi

Description

Local Area Network Cable

Cat. 6A U/UTP 4x2xAWG23/1

Coaxial Cables

CAVEL[®]

since 1968

Data Sheet

LAN6A40

Characteristic impedance	100 MHz	100 ± 5	Ohm
Capacitance of Twisted Pair (@800Hz)		48	pF/m
Velocity Ratio		67 %	
DC Conductor Resistance		80	Ohm/km
Loop resistance		160	Ohm/km
Insulation resistance		> 5000	MOhm/km
Sheath Insulation Voltage (DC, 1 min)		1	kV
Coupling Attenuation		> 45	dB

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	RL [dB]	NEXT [dB]	ACR [dB/100m]
1	1,80	25,00	100,00	98,20
10	5,40	25,00	80,00	74,60
20	7,70	25,00	70,00	62,30
31,2	9,60	25,00	65,00	55,40
62,5	13,70	25,00	60,00	46,30
100	17,40	25,00	60,00	42,60
155,5	21,90	25,00	55,00	33,10
200	25,00	20,00	55,00	30,00
250	28,10	20,00	50,00	21,90
300	30,80	20,00	45,00	14,20
500	40,00	15,00	42,00	2,00

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date

30/05/2017

Responsible

Alberto Scardovi