

Description

Security video cable - 75 Ohm

LSZH UV resistant security video cable (Screening Class A)

Coaxial Cables

CAVEL®

since 1968

Data Sheet

VSHD113



Ø	1,13	4,80	4,90	5,30	6,60
	(Cu)	(PEG)	(Al/Pet/Al)	(CuSn)	(LSZH)

Class CPR acc. to UE 305/2011 (DoP)

Dca s2,d2,a1

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Reaction to Fire

EN 50575

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 ± 0,10	mm
Aluminum/Polyester/Aluminum tape longitudinally overlapped	(Al/Pet/Al)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		72	%
Diameter over Braid		Ø 5,30	mm
Outer sheath of Thermoplastic material - blue (RAL 5015) - halogen-free, low smoke, flame retardant and UV-resistant	(LSZH)	Ø 6,60 ± 0,10	mm

Printed each meter by blue ink-jet :

CAVEL VS HD 113 LSZH MADE IN ITALY 75 Ohm Euroclass Dca,s2,d2,a1 EN50117-2-5 CEI-UNEL 36762

C-4 (U0 = 400V) gggaa(n) m

(ggg=day)(aa=year)(n=batch) (m=meter marking)

Physical data

Weight of copper conductors	19,20	kg/km
Total weight of cable	45,23	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Maximum cable pulling strength	150	N
Minimum installation temperature	-5	°C
Operating temperature	-25 / +80	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		18	Ohm/km
Outer conductor resistance		13,90	Ohm/km
Loop resistance		31,90	Ohm/km
Sheat Insulation voltage (spark test)		3	kV
Maximum current (Ieff)		8	A

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

Alberto Scardovi

Description

Security video cable - 75 Ohm

LSZH UV resistant security video cable (Screening Class A)



Data Sheet

VSHD113

Maximum Operating Range analog/digital 1500 / 300 m

Structural return loss (SRL)

5 - 470 MHz	>30 dB
470 - 1000 MHz	>28 dB
1000 - 2000 MHz	>26 dB
2000 - 3000 MHz	>22 dB

Screening Attenuation (SA)

SA-Class A+

Transfer Impedance (Zt)

Zt-Class A

30 - 1000 MHz	>95 dB
1000 - 2000 MHz	>85 dB
2000 - 3000 MHz	>75 dB

5 - 30 MHz < 5 mOhm/m


Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
2	1,00	5	1,60
3	1,20	200	8,00
4	1,40	862	17,10

Attenuazione di schermatura / Screening Attenuation

Cavo classe A+ / A+ Class Cable

Cavo tipo / Cable type : VS HD 113



Connectors

BNCC5.1C

Series BNC Compression, BNC Compression, for OUTDOOR installation

BNCC703

Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

Alberto Scardovi