

DATA SHEET

item no. **BNCCEM3C**

connector type
For cable

BNC MALE COMPRESSION 75Ω
VSHD40, CW41S

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating	5 A
Shielding Effectiveness	> 120 dB @ 1GHz



Return Loss (IEC 169.1.1)
(RF Analyzer E8357A)

0.3 - 500 MHz	- 34.0 dB
500 - 860 MHz	- 30.7 dB
860 - 1000 MHz	- 26.7 dB
1000 - 1750 MHz	- 23.4 dB
1750 - 2150 MHz	- 21.7 dB
2150 - 3000 MHz	- 19.8 dB

Insertion Loss Max.

0.3 - 500 MHz	< 0.07 dB
500 - 860 MHz	< 0.10 dB
860 - 1000 MHz	< 0.14 dB
1000 - 1750 MHz	< 0.18 dB
1750 - 2150 MHz	< 0.20 dB
2150 - 3000 MHz	< 0.26 dB

Temperature
Installing
Operating
Storing

- 5° to + 50° C
- 40° to + 100° C
- 40° to + 100° C

Inner Conductor

Resistance max. @1 A DC **<1 mOhm**

Max. Tensile Strength
Overall

220 N

Base Material

Body parts **Brass CuZn 39Pb3 / Zinc**
Inner conductor **Brass CuZn 39Pb3**

Inner Conductor

O-ring

EPDM

Plating

Body parts **Nitin**
Inner conductor **Gold**

Color

BLACK

Date of release

March 30 . 2016



ITALIANA CONDUTTORI S.r.l.

Viale Zanotti, 90

I - 27027 Gropello Cairoli (PV)

Tel. +39 0382 815 150 - Fax +39 0382 814 970

www.cavel.com - cavel@cavel.it